



*A global leader in agitation agglomeration technology —  
the conversion of fine powders and dusts  
into spherical pellets.*

## DP-14 “Agglo-Miser”

The “Agglo-Miser” laboratory pelletizer is a multi-depth, bench-scale unit which permits a wide range of test conditions for powder and dust pelletizing. It is designed to provide three adjustable pan depths, and a selection of pan speeds and pan angle variations up to 60° maximum.

The “Agglo-Miser” can be operated either as a shallow disc or a deep drum to produce either micropellets, granules, or large balls.

### Application

The compact size of the “Agglo-Miser” is well suited for granulation and pelletizing of laboratory quantities. Tests can be effectively conducted on chemicals, pharmaceuticals, foodstuffs, detergents, pigments, ceramics, glass mix, cement, fertilizer, mineral and metal fines, coal and flue dust. Small batches of pellets may be produced continuously at low, medium, and deep pan settings by means of a basic 3” deep pan with two adapter rings for 6” and 9” depths.



DP-14 Agglo-Miser	Used as Pelletizer	Used as Mixer	End Product		Typical Operating Ranges		Capacity
			Size	Shape	Drum	Disk	
	Yes	No	0.03 – 1.5 in. dia. 0.85 – 38.1 mm	Spherical	0 – 30°	40-60°	0.20-0.80 ft <sup>3</sup> /hr 0.006-0.02 m <sup>3</sup> /hr

### DP-14 Specifications

**Pan Diameter:** 14”

**Pan Depth:** 3”, 6”, 9” adjustable.

**Pan Speed:** 5-50 RPM.

**Pan Angle:** Horizontal to 60° maximum.

**Drive:** DC/SCR control drive, 1/8HP, 50/60 Hz, 120/230 volt, 1 phase.

**Scrapers:** Two types for drum or pan type operation.

**Contact Materials:** Pan, rings and scrapers are made of type 304 stainless steel.

**Spray System (optional):** Piping, needle valve, pressure gauge, flexible tubing and nozzle.

128 Myoma Road  
Mars, PA 16046  
tel: 724-538-3000  
fax: 724-538-5078  
info@marsmineral.com  
[www.marsmineral.com](http://www.marsmineral.com)